

Project Information

Project Name	Temperature Evaluation Corkonut						
Client Info	Greenplay Sports 6 Hawthorne Avenue Merrick, NY 11566						
Report Date	12/8/2017		Test Date	11/16/2017			
Report Status	Final		Job no.	92874/3006			
Prepared by		Kieran O'Donnell Field Operation Manager					
Checked by		Jeffrey Gentile Laboratory Director		Master			

Notes:

- 1. This report has been prepared by Sports Labs USA with all reasonable skill, care and diligence within the terms of the contract with the Client and within the limitations of the resources devoted to it.
- 2. This report is confidential to the Client and Sports Labs USA accepts no responsibility whatsoever to third parties to whom this report, or any part thereof, is made known. Any such party relies upon the report at their own risk.
- 3. This report shall not be used for engineering or contractual purposes unless signed by the Author and the Checker and unless the report status is "Final."

Introduction

Sports Labs USA was commissioned to perform a temperature evaluation per FIFA Test Method 14. Complete results and background can be found in subsequent sections of this report.

Summary

The following testing was performed to determine the relative effect infill can have on the surface temperature of a synthetic turf system. Synthetic turf carpet with infill was exposed to infra-red heat lamps for a prolonged period to simulate the heating of the sun in a controlled environment per FIFA Test Method 14 heating apparatus. The resulting temperatures were observed and recorded.



















Procedure

- Each system was constructed and prepared per EN 12229: Surfaces for sports areas Procedure for the preparation of synthetic turf and textile pieces.
- Each system was constructed using the infill combinations shown in the systems description table below.
- The samples were conditioned to room temperature for at least 24 hours.

Heat Test

The following sensors were used to capture and record measurements to a digital data logger every 5 minutes:

- (3) Infra-red thermo-couples aimed at the sample to register surface temperature.
- (1) thermo-couple placed underneath the center of the turf backing.
- (1) Environmental meter for air temperature and humidity.

The samples were heated for 3 hours. All the data was compiled and the temperatures for each phase were found. This report will present the temperature recorded at each sensor as well as the average for each type of temperature measurement sensor. Final lux measurement after 180 minutes elapsed time was 2650. The maximum surface temperature reached was 113 °F, which falls into category 1.

Reference

The chart below shows tolerance categories for the FIFA 14 heat test method

Category	Temperature Range °F
Category 1	<122
Category 1-2	122-130
Category 2	131-139
Category 2-3	140-149
Category 3	>149



















System Description

System ID	System Description
	Synthetic Turf Carpet: 2 3/8" Turf
EcoMax	Infill Combination: 2.25 lbs. per sq. ft. Corkonut/4 lbs. per sq. ft. Sand

Results

Temperature and Humidity per phase									
Phase	Elapsed Time (min)	Ambient Air Temp (°F)	Specimen Surface Temp (°F)	Backing Center Temp (°F)	Humidity (%)				
1	0	72	66	67	34				
	5	73	72	66	34				
	10	74	79	66	33				
	15	75	86	66	32				
	20	76	90	66	32				
2	30	78	93	68	31				
	40	80	95	69	31				
	50	81	96	70	30				
	60	82	98	71	29				
	75	83	101	73	28				
	90	85	103	75	28				
	105	86	104	76	28				
3	120	86	106	77	28				
	135	88	107	79	27				
	150	88	109	79	28				
	165	89	111	80	29				
	180	89	113	81	30				

















































End of Report















